

View Online at <https://aerobasegroup.com/nsn/5930-00-900-7308>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

5.500 inches

**Outside Diameter:**

0.540 inches single connection

**Overall Height:**

1.500 inches

**Overall Width:**

1.920 inches

**Body Diameter:**

1.370 inches

**Body Length:**

3.009 inches

**Unthreaded Mounting Hole Diameter:**

0.190 inches

**Distance Between Mounting Facility Centers:**

0.500 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between 0.0 degrees fahrenheit and 165.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

3000.00 pounds per square inch gage

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Sensing Element Burst Pressure:**

5000.00 pounds per square inch gage

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

2.5 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

47.00 actuation point pounds per square inch gage and 53.00 actuation point pounds per square inch gage

**Contact Voltage Rating In Volts:**

120.0 ac at sea level single voltage

**Pressure Connector Type:**

Plain, unthreaded external single connection

**Media For Which Designed:**

Gas

**Style Designator:**

Cylindrical w/mounting lugs

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A048b0