

View Online at <https://aerobasegroup.com/nsn/5930-00-900-7308>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

5.500 inches

Outside Diameter:

0.540 inches single connection

Overall Height:

1.500 inches

Overall Width:

1.920 inches

Body Diameter:

1.370 inches

Body Length:

3.009 inches

Unthreaded Mounting Hole Diameter:

0.190 inches

Distance Between Mounting Facility Centers:

0.500 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between 0.0 degrees fahrenheit and 165.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

3000.00 pounds per square inch gage

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

5000.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

2.5 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

47.00 actuation point pounds per square inch gage and 53.00 actuation point pounds per square inch gage

Contact Voltage Rating In Volts:

120.0 ac at sea level single voltage

Pressure Connector Type:

Plain, unthreaded external single connection

Media For Which Designed:

Gas

Style Designator:

Cylindrical w/mounting lugs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0