

View Online at <https://aerobasegroup.com/nsn/5930-00-901-4656>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Weatherproof

Bushing Length:

Between 0.458 inches and 0.478 inches

Body Length:

1.336 inches

Body Width:

0.734 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.237 inches and 0.243 inches

Actuator Height:

Between 0.655 inches and 0.719 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary, two positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 25.000 amperes resistive ac and 15.000 amperes inductive ac and 7.000 amperes lamp ac

Test Data Document:

81349-mils8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0