

View Online at <https://aerobasegroup.com/nsn/5930-00-901-5160>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Watertight

Body Diameter:

Between 0.970 inches and 1.030 inches

Bushing Length:

Between 1.270 inches and 1.330 inches

Body Length:

1.500 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.370 inches and 0.380 inches

Actuator Height:

Between 1.645 inches and 1.705 inches

Actuator Free Position Height:

0.375 inches

Actuator Adapter Style:

Pushbutton

Adapter Bushing Length:

Between 1.270 inches and 1.330 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thread Size:

0.750 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 96.0 ounces and 192.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.250 overtravel inches and 0.015 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc

Test Data Document:

81349-mil-prf-8805/41 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0

Mil-std (military Standard):

Mil-prf-8805 spec.