NSN 5930-00-901-7422

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-901-7422

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Moisture resistant
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.750 inches
Body Length:
1.062 inches
Body Width:
0.562 inches
Body Height:
0.812 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.500 inches
Actuator Style:
Round
Actuator Diameter:
0.125 inches
Actuator Height:
0.188 inches
Maximum Voltage Rating In Volts:
125.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.5 inch-ounces
Switch Actuating Force:
4.0 inch-ounces
Actuator Movement:
Between 30.0 pretravel degrees and 18.0 overtravel degrees and 8.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive ac
Terminal Type And Quantity:

3 tab, solder lug

NSN 5930-00-901-7422

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0