

View Online at <https://aerobasegroup.com/nsn/5930-00-901-8211>

**Body Style:**

Hole mounted

**Overall Length:**

1.940 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.984 inches and 1.016 inches

**Overall Height:**

1.300 inches

**Overall Width:**

0.687 inches

**Body Length:**

Between 1.922 inches and 1.954 inches

**Body Width:**

Between 0.672 inches and 0.704 inches

**Body Height:**

Between 0.859 inches and 0.891 inches

**Case Material:**

Metal

**Unthreaded Mounting Hole Diameter:**

Between 0.139 inches and 0.142 inches

**Actuator Length:**

0.630 inches

**Actuator Style:**

Leaf

**Actuator Width:**

Between 0.078 inches and 0.110 inches

**Actuator Free Position Height:**

Between 0.610 inches and 0.640 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**End Application:**

Zspruance class dd (963), sturgeon class ssn (637), forrestal class cv, shipboard material handling equipment (mhe), elevators, cargo/weapons, nimitz cvn, los angeles class ssn (688), ticonderoga class cg (47), arleigh burke class ddg

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

5.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

Between 12.0 ounces and 18.0 ounces

**Actuator Movement:**

Between 0.035 pretravel inches and 0.005 overtravel inches and 0.006 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0