## NSN 5930-00-902-2505

Push Switch - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5930-00-902-2505

| Panel mount                                     |
|---|
| Hazardous Locations/environmental Protection:   |
| Moisture resistant                              |
| Overall Length:                                 |
| 1.000 inches                                    |
| Overall Height:                                 |
| 3.093 inches                                    |
| Overall Width:                                  |
| 0.750 inches                                    |
| Body Length:                                    |
| 0.905 inches                                    |
| Body Width:                                     |
| 0.750 inches                                    |
| Case Material:                                  |
| Metal   |
| Actuator Length:                                |
| 0.680 inches                                    |
| Actuator Style:                                 |
| Rectangular                                     |
| Actuator Height:                                |
| 0.180 inches                                    |
| Actuator Width:                                 |
| 0.430 inches                                    |
| Actuator Color:                                 |
| Green single actuator and white single actuator |
| Illuminated Actuator Color:                     |
| Green single actuator and white single actuator |
| Actuator Inscription:                           |
| Ajac, selected, channels single actuator        |
| Maximum Voltage Rating In Volts:                |
| 115.0 ac and 28.0 dc                            |
| Inclosure Type:                                 |
| Fully enclosed                                  |
| Mounting Method:                                |
| Panel   |
| Features Provided:                              |
| Holding solenoid                                |

**Nonpile-up Contact Arrangement:** 

**Contact Load Current Rating At Maximum Rated Voltage:** 

4 pole, double throw, one position momentary single switch unit

3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.000 amperes lamp dc and 3.000 amperes resistive ac

## NSN 5930-00-902-2505

Push Switch - Page 2 of 2

**Precious Material And Location:** 



| Contacts gold and contacts silver     |
|---------------------------------------|
| Unable To Decode:                     |
| Unable to decode and unable to decode |
| Terminal Type And Quantity:           |
| 17 tab, solder lug                    |
| Shelf Life:                           |

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0