NSN 5930-00-902-2526

Push Switch - Page 1 of 2

Body Style:Panel mount



View Online at https://aerobasegroup.com/nsn/5930-00-902-2526

| Hazardous Locations/environmental Protection: |
|---|
| Moisture resistant |
| Overall Length: |
| 1.000 inches |
| Overall Height: |
| 3.093 inches |
| Overall Width: |
| 0.750 inches |
| Body Length: |
| 0.905 inches |
| Body Width: |
| 0.750 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 0.680 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.180 inches |
| Actuator Width: |
| 0.430 inches |
| Actuator Color: |
| Green single actuator and white single actuator |
| Illuminated Actuator Color: |
| Green single actuator and white single actuator |
| Actuator Inscription: |
| Manual, channel, select single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| |

Contact Load Current Rating At Maximum Rated Voltage:

4 pole, double throw, one position momentary single switch unit

Nonpile-up Contact Arrangement:

3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.000 amperes lamp dc and 3.000 amperes resistive ac

NSN 5930-00-902-2526

Push Switch - Page 2 of 2



| Precious | Material | And | Location: |
|----------|----------|-----|-----------|
|----------|----------|-----|-----------|

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

17 tab, solder lug

,

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0