NSN 5930-00-902-8890

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-902-8890

Overall Length:
5.875 inches
Overall Height:
3.875 inches
Overall Width:
3.344 inches
Body Length:
5.875 inches
Unthreaded Mounting Hole Diameter:
0.219 inches
Capillary Tube Length:
84.0 inches
Bulb Length:
11.250 inches
Bulb Diameter:
0.188 inches
Longest Horizontal Distance Between Mounting Centers:
2.438 inches
Longest Vertical Distance Between Mounting Centers:
3.875 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Base and unthreaded hole
Features Provided:
Pilot light
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
2 pole, single throw, normally closed, momentary action
Terminal Type:
Tab w/screw
Contact Load Current Rating:
35.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+50.00/+250.00 actuation point degrees fahrenheit and +50.00/+250.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point knob with scale and external actuation point knob with scale

NSN 5930-00-902-8890

Thermostatic Switch - Page 2 of 2



Contact voltage Rating in volts:
120.0 ac at sea level single voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A048b0