NSN 5930-00-903-3424 Sensitive Switch - Page 1 of 2



| Constitute Owner 1 age 1 of 2 | |
|--|--|
| View Online at https://aerobasegroup.com/nsn/5930-00-903-3424 | |
| Body Style: | |
| Hole mounted | |
| Overall Length: | |
| 0.781 inches | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | |
| Between 0.373 inches and 0.377 inches | |
| Overall Height: | |
| 0.537 inches | |
| Overall Width: | |
| 0.250 inches | |
| Body Length: | |
| Between 0.771 inches and 0.791 inches | |
| Body Width: | |
| Between 0.240 inches and 0.260 inches | |
| Body Height: | |
| Between 0.349 inches and 0.369 inches | |
| Unthreaded Mounting Hole Diameter: | |
| Between 0.087 inches and 0.090 inches | |
| Actuator Style: | |
| Leaf | |
| Actuator Free Position Height: | |
| Between 0.335 inches and 0.365 inches | |
| Maximum Voltage Rating In Volts: | |
| 250.0 ac and 30.0 dc | |
| Inclosure Type: | |
| Fully enclosed | |
| Mounting Method: | |
| Unthreaded hole | |
| Nonpile-up Contact Arrangement: | |
| 1 pole, double throw, one position momentary single switch unit | |
| Switch Release Force: | |
| 1.0 ounces | |
| Switch Actuating Force: | |
| 8.0 ounces | |
| Actuator Movement: | |
| 0.094 pretravel inches and 0.040 overtravel inches and 0.031 differential inches | |
| Contact Load Current Pating At Maximum Pated Voltage: | |

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

NSN 5930-00-903-3424 Sensitive Switch - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

Demilitarization:

No

Fiig:

A053a0