NSN 5930-00-903-5203

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-903-5203

Body Style:

Hole mounted

Overall Length:

1.950 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Overall Height:

0.930 inches

Overall Width:

0.400 inches

Body Length:

1.094 inches

Body Width:

0.400 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Length:

1.020 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.404 inches

Actuator Roller Diameter:

0.190 inches

Actuator Roller Width:

0.190 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

8.0 ounces

NSN 5930-00-903-5203

Sensitive Switch - Page 2 of 2



Actuator Movement:

Between 0.125 pretravel inches and 0.062 overtravel inches and 0.050 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

 $250.000\ \text{milliamperes}$ resistive dc and $15.000\ \text{amperes}$ resistive ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0