

View Online at <https://aerobasegroup.com/nsn/5930-00-904-0521>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.139 inches

Actuator Style:

Round

Actuator Diameter:

0.094 inches

Actuator Free Position Height:

Between 0.600 inches and 0.630 inches

Actuator Adapter Style:

Roller arm

Housing Height:

1.750 inches

Housing Length:

3.040 inches

Housing Width:

1.000 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.000 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Switch Release Force:

6.0 ounces

Switch Actuating Force:

30.0 ounces

Actuator Movement:

Between 266.0 pretravel millimeters and 219.0 overtravel millimeters and 165.0 differential millimeters

Contact Load Current Rating At Maximum Rated Voltage:

150.000 milliamperes resistive dc and 10.000 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0