

View Online at <https://aerobasegroup.com/nsn/5930-00-904-0524>

Body Style:

Bushing mount

Overall Length:

0.840 inches

Overall Height:

2.538 inches

Overall Width:

0.719 inches

Bushing Length:

Between 0.455 inches and 0.485 inches

Body Length:

Between 0.825 inches and 0.855 inches

Body Width:

0.719 inches

Body Height:

Between 0.916 inches and 0.976 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.418 inches and 0.438 inches

Actuator Height:

1.180 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position locked in and down position locked in and center position locked out

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0