

View Online at <https://aerobasegroup.com/nsn/5930-00-904-1921>

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

1.250 inches

Overall Height:

0.440 inches

Overall Width:

0.401 inches

Mounting Slot Width:

0.125 inches

Body Length:

0.776 inches

Body Width:

0.401 inches

Body Height:

0.251 inches

Distance Between Mounting Facility Centers:

1.000 inches

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Clip and slot

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

2.5 amperes resistive load first voltage 2.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+20.00/+200.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

75.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

115.0 ac at sea level first voltage 28.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0