

View Online at <https://aerobasegroup.com/nsn/5930-00-904-2026>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

Between 0.495 inches and 0.515 inches

Overall Height:

Between 1.091 inches and 1.164 inches

Bushing Length:

Between 0.239 inches and 0.253 inches

Body Length:

Between 0.495 inches and 0.515 inches

Body Width:

Between 0.246 inches and 0.265 inches

Body Height:

Between 0.313 inches and 0.337 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

Between 0.077 inches and 0.079 inches

Actuator Height:

Between 0.275 inches and 0.301 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

50.0 dc

Mounting Surface To Terminal End Distance:

0.705 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0