NSN 5930-00-904-7605

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-904-7605

Body Style:

Hole mounted

Overall Length:

0.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.188 inches

Overall Height:

0.470 inches

Overall Width:

0.200 inches

Body Length:

0.500 inches

Body Width:

0.200 inches

Body Height:

0.350 inches

Unthreaded Mounting Hole Diameter:

0.087 inches

Actuator Style:

Round

Actuator Diameter:

0.063 inches

Actuator Height:

0.030 inches

Actuator Free Position Height:

0.320 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc

NSN 5930-00-904-7605

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0