NSN 5930-00-905-0604

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-905-0604

| Overall Length: |
|---|
| 5.563 inches |
| Overall Height: |
| 2.250 inches |
| Overall Width: |
| 2.375 inches |
| Mounting Slot Width: |
| 0.125 inches |
| Body Length: |
| 4.375 inches |
| Bulb Length: |
| 5.000 inches |
| Bulb Diameter: |
| 0.375 inches |
| Longest Horizontal Distance Between Mounting Centers: |
| 1.562 inches |
| Longest Vertical Distance Between Mounting Centers: |
| 2.938 inches |
| Tempurature Sensing Element Type: |
| Bulb |
| Mounting Method: |
| Base and slot |
| Contact Action Stimulus: |
| Increase |
| Mounting Facility Pattern: |
| Four position rectangular |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary |
| Terminal Type: |
| Screw |
| Contact Load Current Rating: |
| 8.0 amperes resistive load first voltage |
| Contact Adjustability: |
| Deactuation point adjustable and actuation point adjustable |
| Contact Adjustment Range: |
| +30.00/+110.00 actuation point degrees fahrenheit and +30.00/+110.00 deactuation point degrees fahrenheit |
| Contact Adjustment Type: |
| External deactuation point knob and external actuation point knob |
| Contact Voltage Rating In Volts: |
| 240.0 ac at sea level first voltage |
| Media For Which Designed: |

Gas or liquid

NSN 5930-00-905-0604

Thermostatic Switch - Page 2 of 2



| Style Designator: |
|-------------------|
| Rectangular |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A048b0