

View Online at <https://aerobasegroup.com/nsn/5930-00-905-0748>

Overall Length:

Any acceptable

Power Cable Length:

Any acceptable

Overall Height:

Any acceptable

Overall Width:

Any acceptable

Ac Voltage Rating:

230.000 volts

Overall Diameter:

Any acceptable

Actuation Method:

Buoyancy

Electrical Connection Type:

Cable

Internal Battery Accommodation:

Not included

Current Rating At Maximum Rated Voltage:

6.5 amperes resistive load

Float Quantity:

2

Operating Temperature Rating:

Between 100.0 degrees fahrenheit and 400.0 degrees fahrenheit

Mounting Method:

Thread

Mounting Position:

Vertical

Contact Arrangement:

Spst normally open

Relay:

Not included

Liquid Type For Which Designed:

Diesel oil

Float Effective Travel:

2.000 inches

Mounting Dimensions:

2-1/2 -8 npt thd connection

Tank Insertion Length:

Any acceptable

Phase:

Single

Special Features:

With 10 ft type 316 stainless steel flexible cable stem, displacement type liquid level control, explosion proof and waterproof switch housing and designed for 3/4 in. Conduit wiring

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T109-d