

View Online at <https://aerobasegroup.com/nsn/5930-00-905-8481>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Salt spray resistant

Bushing Length:

Between 0.234 inches and 0.266 inches

Body Length:

Between 0.484 inches and 0.516 inches

Body Width:

Between 0.234 inches and 0.266 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.175 inches and 0.185 inches

Actuator Height:

Between 0.390 inches and 0.550 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0