## NSN 5930-00-905-8735

**Mounting Method:** 

Isosceles triangle

**Terminal Type:** 

Screw

Increase

Bracket and unthreaded hole Contact Action Stimulus:

**Mounting Facility Pattern:** 

**Nonpile-up Contact Arrangement:** 

**Contact Load Current Rating:** 

Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level second voltage

Media For Which Designed:

Frequency In Hertz: 60.0 first voltage

Gas or liquid

3.2 amperes inductive load first voltage

1 pole, double throw, both positions maintained

+150.00/+225.00 actuation point degrees fahrenheit



Thermostatic Switch - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5930-00-905-8735	
Overall Length:	
5.188 inches	
Overall Height:	
8.625 inches	
Overall Width:	
2.812 inches	
Body Height:	
2.750 inches	
Unthreaded Mounting Hole Diameter:	
0.281 inches	
Longest Horizontal Distance Between Mounting Centers:	
2.812 inches	
Shortest Horizontal Distance Between Mounting Centers:	
0.656 inches	
Longest Vertical Distance Between Mounting Centers:	
3.281 inches	
Tempurature Sensing Element Type:	
Bulb	

## NSN 5930-00-905-8735

Thermostatic Switch - Page 2 of 2



•		
StVID	l Jacian	ator.
OLYIC	Design	atoi.

Rectangular w/bracket

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0