

View Online at <https://aerobasegroup.com/nsn/5930-00-906-0327>

**Hazardous Locations/environmental Protection:**

Splashproof

**Overall Length:**

10.750 inches

**Overall Height:**

3.750 inches

**Overall Width:**

4.750 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.406 inches

**Shortest Horizontal Distance Between Mounting Centers:**

0.656 inches

**Longest Vertical Distance Between Mounting Centers:**

3.281 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

150.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

7200.00 pounds per square inch gage

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Screw

**Contact Load Current Rating:**

0.5 amperes resistive load second voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+240.00/+5000.00 actuation point pounds per square inch gage

**Contact Adjustment Type:**

Internal actuation point screw

**Contact Voltage Rating In Volts:**

115.0 dc at sea level second voltage

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0