

View Online at <https://aerobasegroup.com/nsn/5930-00-906-1436>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Industrial use

**Actuator Style:**

Roller arm

**Actuator Roller Diameter:**

Between 0.720 inches and 0.780 inches

**Actuator Roller Width:**

0.280 inches

**Housing Height:**

Between 1.532 inches and 1.592 inches

**Housing Length:**

Between 3.640 inches and 3.760 inches

**Housing Width:**

Between 1.540 inches and 1.600 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

Between 2.295 inches and 2.325 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

Between 1.175 inches and 2.205 inches

**Maximum Voltage Rating In Volts:**

460.0 ac and 230.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

8.0 inch-ounces

**Switch Actuating Force:**

48.0 inch-ounces

**Actuator Movement:**

Between 20.0 pretravel degrees and 30.0 overtravel degrees and 12.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

400.000 milliamperes resistive dc and 10.000 amperes resistive ac

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0