

View Online at <https://aerobasegroup.com/nsn/5930-00-906-1436>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Industrial use

Actuator Style:

Roller arm

Actuator Roller Diameter:

Between 0.720 inches and 0.780 inches

Actuator Roller Width:

0.280 inches

Housing Height:

Between 1.532 inches and 1.592 inches

Housing Length:

Between 3.640 inches and 3.760 inches

Housing Width:

Between 1.540 inches and 1.600 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

Between 2.295 inches and 2.325 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

Between 1.175 inches and 2.205 inches

Maximum Voltage Rating In Volts:

460.0 ac and 230.0 dc

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

8.0 inch-ounces

Switch Actuating Force:

48.0 inch-ounces

Actuator Movement:

Between 20.0 pretravel degrees and 30.0 overtravel degrees and 12.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

400.000 milliamperes resistive dc and 10.000 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0