

View Online at <https://aerobasegroup.com/nsn/5930-00-906-1735>

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

Between 4.031 inches and 4.405 inches

Body Diameter:

Between 0.618 inches and 0.625 inches

Body Length:

Between 3.656 inches and 3.780 inches

Overall Diameter:

0.656 inches

Temperature Sensing Element Type:

Expanding shell

Operating Temperature Rating:

Between -73.0 degrees celsius and 416.0 degrees celsius

Mounting Method:

Immersion well

Contact Action Stimulus:

Increase

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

10.0 amperes resistive load first voltage5.0 amperes resistive load second voltage2.0 amperes resistive load third voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

-73.00/+316.00 actuation point degrees celsius and -73.00/+316.00 deactuation point degrees celsius

Contact Adjustment Type:

External actuation point screw and external deactuation point screw

Contact Voltage Rating In Volts:

120.0 ac at sea level first voltage240.0 ac at sea level second voltage115.0 dc at sea level third voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0