NSN 5930-00-906-3273

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-906-3273

Body Style:
Bushing/hole mounted
Overall Length:
1.938 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
1.765 inches
Overall Width:
0.688 inches
Bushing Length:
0.516 inches
Body Length:
1.938 inches
Body Width:
0.688 inches
Body Height:
0.891 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Round
Actuator Diameter:
0.328 inches
Actuator Height:
0.344 inches
Actuator Free Position Height:
0.874 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing and unthreaded hole
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:

4.0 ounces

NSN 5930-00-906-3273

Sensitive Switch - Page 2 of 2



Switch Actua	ting Force:
--------------	-------------

Between 9.0 ounces and 13.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0