NSN 5930-00-906-3289

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-906-3289

Thread Class:
2b single mounting facility
Overall Length:
2.376 inches
Overall Height:
2.750 inches
Overall Width:
2.750 inches
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
0.938 inches single actuator
Unthreaded Mounting Hole Diameter:
0.164 inches single mounting facility
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
1.500 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
3 single section rear
3 single section rear Throw Quantity:
-
Throw Quantity:
Throw Quantity: 12 single section rear
Throw Quantity: 12 single section rear Mounting Method:
Throw Quantity: 12 single section rear Mounting Method: Bracket single mounting facility and threaded hole single mounting facility
Throw Quantity: 12 single section rear Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Thready Qty Per Inch (tpi):
Throw Quantity: 12 single section rear Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility
Throw Quantity: 12 single section rear Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size:
Throw Quantity: 12 single section rear Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.164 inches single mounting facility
Throw Quantity: 12 single section rear Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.164 inches single mounting facility Contact Voltage Rating In Volts:
Throw Quantity: 12 single section rear Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.164 inches single mounting facility Contact Voltage Rating In Volts: 115.0 ac at sea level
Throw Quantity: 12 single section rear Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.164 inches single mounting facility Contact Voltage Rating In Volts: 115.0 ac at sea level Mounting Facility Pattern:
Throw Quantity: 12 single section rear Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.164 inches single mounting facility Contact Voltage Rating In Volts: 115.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility
Throw Quantity: 12 single section rear Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.164 inches single mounting facility Contact Voltage Rating In Volts: 115.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity:
Throw Quantity: 12 single section rear Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.164 inches single mounting facility Contact Voltage Rating In Volts: 115.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 12 single actuator
Throw Quantity: 12 single section rear Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.164 inches single mounting facility Contact Voltage Rating In Volts: 115.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 12 single actuator Shaft Type:
Throw Quantity: 12 single section rear Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.164 inches single mounting facility Contact Voltage Rating In Volts: 115.0 ac at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 12 single actuator Shaft Type: Round single actuator

Breaks before makes single section rear

NSN 5930-00-906-3289

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

15.0 degrees single actuator

Contact Load Current Rating:

2.0 amperes resistive load ac at sea level

Style Designator:

Tap, square frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0