NSN 5930-00-906-3345

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-906-3345

Overall Length:
3.380 inches
Overall Diameter:
1.250 inches
Pressure Switch Type:
Gage
Width Across Flats:
1.250 inches
Mounting Method:
Inlet connection
Features Provided:
Electrical box connector
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
4500.00 pounds per square inch
Thread Size:
0.438 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Sensing Element Burst Pressure:
7500.00 pounds per square inch
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
5.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable, preset and actuation point adjustable, preset
Contact Adjustment Range:
+0.00/+1750.00 actuation point pounds per square inch and +0.00/+1750.00 deactuation point pounds per square inch
Contact Adjustment Type:
Internal deactuation point screw and internal actuation point screw
Contact Stimulus Rating:
1500.00 actuation point pounds per square inch and 1750.00 deactuation point pounds per square inch and 250.00 differential point
pounds per square inch
Contact Voltage Rating In Volts:
28.0 dc at sea level single voltage
Pressure Connector Type:

Gas or liquid

Media For Which Designed:

Inverted flare, threaded external single connection

NSN 5930-00-906-3345

Pressure Switch - Page 2 of 2



Style Designator:	Style	Design	ator:
-------------------	-------	--------	-------

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0