

View Online at <https://aerobasegroup.com/nsn/5930-00-906-3345>

Overall Length:

3.380 inches

Overall Diameter:

1.250 inches

Pressure Switch Type:

Gage

Width Across Flats:

1.250 inches

Mounting Method:

Inlet connection

Features Provided:

Electrical box connector

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

7500.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+0.00/+1750.00 actuation point pounds per square inch and +0.00/+1750.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Stimulus Rating:

1500.00 actuation point pounds per square inch and 1750.00 deactuation point pounds per square inch and 250.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Inverted flare, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0