

View Online at <https://aerobasegroup.com/nsn/5930-00-906-3431>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Fungus proof

Bushing Length:

Between 0.335 inches and 0.355 inches

Body Length:

Between 0.765 inches and 0.795 inches

Body Width:

0.656 inches

Body Height:

0.582 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.183 inches and 0.193 inches

Actuator Height:

0.595 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0