# NSN 5930-00-906-3462

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-906-3462

## Thread Class:

2a single mounting facility

### Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

1.750 inches

#### **Overall Height:**

1.016 inches

#### **Overall Width:**

0.938 inches

#### First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.216 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

## Shaft Length:

0.750 inches single actuator

#### **Nonturn Device Radius:**

0.375 inches at 3: 00 o'clock

## Individual Section Quantity:

1

#### Nonturn Device Type:

Pin at 3: 00 o'clock

#### **Operating Tempurature Range:**

-65.0/+125.0 degrees celsius

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 single section front

#### **Throw Quantity:**

12 single section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## Shaft Flat/slot Angular Location:

135.0 degrees from nonturn device single actuator

### **Rotor Through Connection Quantity:**

1 single section

## NSN 5930-00-906-3462

Rotary Switch - Page 2 of 2



## Switch Actuator Indexing Position Quantity:

12 single actuator

## Shaft Type:

Round, flatted single actuator

## **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes single section rear

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

## **Contact Load Current Rating:**

50.0 milliamperes resistive load ac at altitude

## Style Designator:

Circular wafer, bushing mount

## Test Data Document:

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A052b0