## NSN 5930-00-906-6199

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-906-6199

Threa	ad I	end	ath:
11116	au L	.6111	4111.

0.430 inches single mounting facility

Width Between Flats:

0.250 inches single actuator

**Hazardous Locations/environmental Protection:** 

Dustproof

**Overall Length:** 

1.310 inches

First Flat Length:

0.210 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.800 inches single actuator

**Overall Diameter:** 

1.036 inches

**Individual Section Quantity:** 

2

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 each section front

**Throw Quantity:** 

5 each section front

**Mounting Method:** 

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

5 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes each section front

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

## NSN 5930-00-906-6199

Rotary Switch - Page 2 of 2



Contact Load	Current	Rating:
--------------	---------	---------

1.0 amperes resistive load dc at sea level

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A052b0