NSN 5930-00-907-2424

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-907-2424

Body Style:
Hole mounted
Overall Length:
1.060 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.750 inches
Overall Height:
0.750 inches
Overall Width:
1.050 inches
Body Length:
1.060 inches
Body Width:
0.560 inches
Body Height:
0.810 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.500 inches
Actuator Style:
Round
Actuator Height:
0.190 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
Between 1.5 grams and 2.5 grams
Switch Actuating Force:
Between 3.0 grams and 4.0 grams
Actuator Movement:

30.0 pretravel degrees and 8.0 overtravel degrees and 3.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes inductive dc

NSN 5930-00-907-2424 Sensitive Switch - Page 2 of 2



Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0