NSN 5930-00-907-5675

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-907-5675 **Thread Class:** 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 1.466 inches **Overall Height:** 1.437 inches **Overall Width:** 1.312 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.375 inches single actuator **Nonturn Device Radius:** 0.437 inches at 9: 00 o'clock **Individual Section Quantity:** 1 **Nonturn Device Type:** Tab at 9: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 single section rear **Throw Quantity:** 4 single section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 4 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Clip **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:**

30.0 degrees single actuator

NSN 5930-00-907-5675

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
1.5 amperes resistive load dc at sea level
Precious Material And Location:
Clips and rotors surface silver
Precious Material:
Silver
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0