NSN 5930-00-907-6995

Rotary Switch Section - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-907-6995

| Overall Height: |
|---|
| 1.328 inches |
| Overall Width: |
| 1.297 inches |
| Body Thickness: |
| 0.062 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.120 inches single mounting facility |
| Longest Horizontal Distance Between Mounting Centers: |
| 1.031 inches single mounting facility |
| Operating Tempurature Range: |
| -65.0/+85.0 degrees celsius |
| Switch Contact Basic Design: |
| Nonpile-up nonsymmetrical |
| Mounting Method: |
| Strut single mounting facility and unthreaded hole single mounting facility |
| Contact Voltage Rating In Volts: |
| 30.0 dc at sea level |
| Mounting Facility Pattern: |
| Two position in-line single mounting facility |
| Terminal Type: |
| Clip |
| Contact Switching Action: |
| Breaks before makes single section rear |
| Contact Load Current Rating: |
| 500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc |
| Precious Material And Location: |
| Clips and rotor blades silver |
| Precious Material: |
| Silver |
| Style Designator: |
| Switch section, rotary |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A052b0 |
| |
| |

at sea level