

View Online at <https://aerobasegroup.com/nsn/5930-00-907-8741>

**Hazardous Locations/environmental Protection:**

Explosion proof and watertight

**Overall Length:**

Between 1.609 inches and 1.641 inches

**Shaft Diameter:**

0.123 inches single actuator and 0.127 inches single actuator

**Shaft Length:**

0.984 inches single actuator and 0.016 inches single actuator

**Overall Diameter:**

Between 0.484 inches and 0.516 inches

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

2 single section rear

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Features Provided:**

Metallic inclosure

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

250.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks single section rear

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

**Style Designator:**

Miniature, bushing mount

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0