

View Online at <https://aerobasegroup.com/nsn/5930-00-908-7612>

Inside Diameter:

0.250 inches single connection

Thread Length:

1.312 inches single pressure connection

Hazardous Locations/environmental Protection:

Dusttight

Overall Length:

4.500 inches

Overall Height:

4.812 inches

Overall Width:

3.500 inches

Body Length:

3.625 inches

Body Height:

3.500 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Longest Horizontal Distance Between Mounting Centers:

4.250 inches

Longest Vertical Distance Between Mounting Centers:

2.875 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

1000.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

15.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+0.00/+100.00 actuation point pounds per square inch and +0.00/+100.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point hex nut and internal actuation point hex nut

Contact Stimulus Rating:

34.00 actuation point pounds per square inch and 3.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

230.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0