# NSN 5930-00-908-9839

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-908-9839

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.250 inches single mounting facility

# **Overall Length:**

11.578 inches

#### **Overall Height:**

1.875 inches

#### **Overall Width:**

1.625 inches

#### Shaft Diameter:

0.250 inches single actuator

## Shaft Length:

0.500 inches single actuator

#### **Nonturn Device Radius:**

## 0.531 inches at 9:00 o'clock

### Individual Section Quantity:

```
3
```

Nonturn Device Type:

Tab at 9: 00 o'clock

### Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

### **Pole Quantity:**

1 3rd section rear

#### Throw Quantity:

3 2nd section front

### **Mounting Method:**

Threaded bushing single mounting facility

### **Thread Size:**

0.375 inches single mounting facility

### Contact Voltage Rating In Volts:

28.0 dc at sea level

### Switch Actuator Indexing Position Quantity:

5 single actuator

## Shaft Type:

Round single actuator

### **Terminal Type:**

Clip

## **Contact Switching Action:**

Makes before breaks 1st section front

# Switch Actuator Positioning Increment:

45.0 degrees single actuator

# NSN 5930-00-908-9839

Rotary Switch - Page 2 of 2



**Detent Rotational Torque Range:** +40.000/+60.000 inch-ounces single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 679.0 milliamperes resistive load ac at sea level **Precious Material And Location:** Clip surfaces gold and clips and rotor blades silver **Precious Material:** Gold and silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A052b0