

View Online at <https://aerobasegroup.com/nsn/5930-00-909-0234>

Overall Length:

2.312 inches

Outside Diameter:

0.125 inches single connection

Body Length:

1.875 inches

Overall Diameter:

0.750 inches

Pressure Switch Type:

Differential

Width Across Flats:

0.750 inches

Operating Temperature Rating:

Between -20.0 degrees fahrenheit and 165.0 degrees fahrenheit

Mounting Method:

Input port

Contact Action Stimulus:

Increase

Proof Pressure:

1500.00 pounds per square inch gage

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+5.00/+10.00 actuation point pounds per square inch gage and +5.00/+10.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal actuation point cam and internal deactuation point cam

Contact Stimulus Rating:

7.50 actuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level third voltage

Pressure Connector Type:

Flared, threaded external single connection

Special Features:

Two potted leads 12 inches long

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0