

View Online at <https://aerobasegroup.com/nsn/5930-00-909-3509>

**Thread Class:**

2b single pressure connection

**Inside Diameter:**

0.312 inches single connection

**Overall Length:**

1.500 inches

**Overall Height:**

3.680 inches

**Overall Width:**

1.500 inches

**Unthreaded Mounting Hole Diameter:**

0.125 inches

**Longest Horizontal Distance Between Mounting Centers:**

1.280 inches

**Longest Vertical Distance Between Mounting Centers:**

1.280 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

-40.0 degrees fahrenheit

**Mounting Method:**

Flush and unthreaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

1100.00 pounds per square inch

**Thread Size:**

0.312 inches single pressure connection

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

2 pole, single throw, normally closed, momentary action

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

500.0 milliamperes resistive load single voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

50.00 actuation point pounds per square inch gage and 40.00 deactuation point pounds per square inch gage

**Contact Voltage Rating In Volts:**

120.0 ac at sea level single voltage

**Pressure Connector Type:**

Double compression, threaded internal single connection

**Special Features:**

Spring operated lever arm assembly

**Frequency In Hertz:**

60.0 single voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0