## NSN 5930-00-909-3509

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-909-3509

Thread Class:
2b single pressure connection
Inside Diameter:
0.312 inches single connection
Overall Length:
1.500 inches
Overall Height:
3.680 inches
Overall Width:
1.500 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Longest Horizontal Distance Between Mounting Centers:
1.280 inches
Longest Vertical Distance Between Mounting Centers:
1.280 inches
Pressure Switch Type:
Gage
Operating Tempurature Rating:
-40.0 degrees fahrenheit
Mounting Method:
Flush and unthreaded hole
Contact Action Stimulus:
Increase
Proof Pressure:
1100.00 pounds per square inch
Thread Size:
0.312 inches single pressure connection
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
2 pole, single throw, normally closed, momentary action
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
500.0 milliamperes resistive load single voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Stimulus Rating:
50.00 actuation point pounds per square inch gage and 40.00 deactuation point pounds per square inch gage
Contact Voltage Rating In Volts:

120.0 ac at sea level single voltage

## **NSN 5930-00-909-3509** Pressure Switch - Page 2 of 2



Pressure Connector Type:
Double compression, threaded internal single connection
Special Features:
Spring operated lever arm assembly
Frequency In Hertz:
60.0 single voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0