

View Online at <https://aerobasegroup.com/nsn/5930-00-909-3509>

Thread Class:

2b single pressure connection

Inside Diameter:

0.312 inches single connection

Overall Length:

1.500 inches

Overall Height:

3.680 inches

Overall Width:

1.500 inches

Unthreaded Mounting Hole Diameter:

0.125 inches

Longest Horizontal Distance Between Mounting Centers:

1.280 inches

Longest Vertical Distance Between Mounting Centers:

1.280 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

-40.0 degrees fahrenheit

Mounting Method:

Flush and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

1100.00 pounds per square inch

Thread Size:

0.312 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

2 pole, single throw, normally closed, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

500.0 milliamperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

50.00 actuation point pounds per square inch gage and 40.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

120.0 ac at sea level single voltage

Pressure Connector Type:

Double compression, threaded internal single connection

Special Features:

Spring operated lever arm assembly

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0