

View Online at <https://aerobasegroup.com/nsn/5930-00-909-3883>

Thread Class:

3a all pressure connection

Overall Length:

3.530 inches

Overall Height:

2.370 inches

Overall Width:

3.540 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Distance Between Mounting Facility Centers:

3.000 inches

Pressure Switch Type:

Gage

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

16 all pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.750 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

7.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

0.50 actuation point gallons per minute and 0.30 deactuation point gallons per minute and 0.20 differential point gallons per minute

Contact Voltage Rating In Volts:

115.0 ac at sea level single voltage

Pressure Connector Type:

Flared, threaded external all connections

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Unf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0