

View Online at <https://aerobasegroup.com/nsn/5930-00-909-6891>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.500 inches single mounting facility

**Overall Length:**

6.050 inches

**Overall Height:**

1.312 inches

**Overall Width:**

Between 1.079 inches and 1.297 inches

**First Flat Length:**

0.375 inches single actuator

**Flat Height:**

0.211 inches single actuator and 0.221 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.625 inches single actuator

**Nonturn Device Radius:**

0.531 inches at 3:00 o'clock

**Individual Section Quantity:**

6

**Nonturn Device Type:**

Tab at 3:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

7 each section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level 300.0 highest ac voltage rating at sea level 15.0 lowest ac voltage rating at sea level

**Switch Actuator Indexing Position Quantity:**

7 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

50.0 milliamperes inductive load dc at sea level and 500.0 milliamperes resistive load dc at sea level 50.0 milliamperes resistive load highest ac voltage rating at sea level 225.0 milliamperes resistive load lowest ac voltage rating at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0