## NSN 5930-00-909-8136

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-909-8136				
Thread Class:				
2a single threaded stud				
Hazardous Locations/environmental Protection:				
Moisture resistant and vibration resistant and salt spray resistant				
Overall Height:				
0.766 inches				
Body Height:				
0.265 inches				
Overall Diameter:				
0.421 inches				
Tempurature Sensing Element Type:				
Internal sensor				
Operating Tempurature Rating:				
Between 32.0 degrees fahrenheit and 176.0 degrees fahrenheit				
Mounting Method:				
Threaded stud				
Features Provided:				
Hermetically sealed case				
Thready Qty Per Inch (tpi):				
40 single threaded stud				
Contact Action Stimulus:				
Decrease				
Thread Size:				
0.112 inches single threaded stud				
Nonpile-up Contact Arrangement:				
1 pole, single throw, normally closed, momentary action				
Terminal Type:				
Tab, solder lug				
Contact Load Current Rating:				
2.0 amperes resistive load third voltage				
Contact Adjustability:				
Actuation point not adjustable and deactuation point not adjustable				
Contact Stimulus Rating:				
9.00 actuation point degrees fahrenheit and 139.00 actuation point degrees fahrenheit and 149.00 deactuation point degrees fahrenheit				
and 159.00 deactuation point degrees fahrenheit				
Contact Voltage Rating In Volts:				
30.0 dc at sea level third voltage				
Media For Which Designed:				
Gas				
Style Designator:				
Disa				

Thread Series Designator: Unc single threaded stud

## NSN 5930-00-909-8136

Thermostatic Switch - Page 2 of 2



-			 
٠.	hΔ	Iŧ.	ife:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0