## NSN 5930-00-909-8768

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-909-8768

**Thread Class:** 

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

**Hazardous Locations/environmental Protection:** 

Explosion proof and watertight

**Overall Length:** 

1.625 inches

**Shaft Diameter:** 

0.125 inches single actuator

**Shaft Length:** 

1.000 inches single actuator

**Overall Diameter:** 

0.500 inches

**Individual Section Quantity:** 

1

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

Pole Quantity:

4 single section rear

**Throw Quantity:** 

2 single section rear

**Mounting Method:** 

Threaded bushing w/panel seal single mounting facility

**Features Provided:** 

Metallic inclosure

Thread Size:

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:** 

250.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

**Shaft Type:** 

Round single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Makes before breaks single section rear

**Switch Actuator Positioning Increment:** 

36.0 degrees single actuator

# NSN 5930-00-909-8768

Rotary Switch - Page 2 of 2



### **Switch Actuator Stop Device Type:**

Fixed stop single actuator

#### **Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

**Style Designator:** 

Snap or line

#### **Thread Series Designator:**

Unf single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0