NSN 5930-00-909-9421

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-909-9421

Thread Class:

2a single mounting facility

Thread Length:

0.438 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.844 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.214 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.438 inches single actuator

Overall Diameter:

1.125 inches

Nonturn Device Radius:

0.375 inches at 3: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clock

Operating Tempurature Range:

-85.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

6 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

0.0 degrees from contact position 1 single actuator

Rotor Through Connection Quantity:

1 single section

NSN 5930-00-909-9421Rotary Switch - Page 2 of 2



Switch Actuator Indexing Position Quantity:
S single actuator
Shaft Type:
Round, flatted single actuator
Ferminal Type:
Гаb, solder lug
Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
36.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
1.0 amperes inductive load dc at sea level
Style Designator:
Гар, circular, bushing mount
Fest Data Document:
31349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Γhread Series Designator:
Unef single mounting facility
Specification Data:
31349-mil-s-3786/4 government specification
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No.
Filg:
A052b0