

View Online at <https://aerobasegroup.com/nsn/5930-00-910-0042>

Inside Diameter:

1.625 inches single connection

Overall Length:

2.368 inches

Overall Height:

1.312 inches

Overall Width:

1.625 inches

Unthreaded Mounting Hole Diameter:

Between 0.150 inches and 0.158 inches

Distance Between Mounting Facility Centers:

1.930 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -73.0 degrees celsius and 150.0 degrees celsius

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

15.75 actuation point pounds per square inch absolute and 14.75 deactuation point pounds per square inch absolute

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Grooved, unthreaded internal single connection

Media For Which Designed:

Gas

Style Designator:

Cylindrical w/lugs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0