## NSN 5930-00-910-0042

Pressure Switch - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5930-00-910-0042
Inside Diameter:
1.625 inches single connection
Overall Length:
2.368 inches
Overall Height:
1.312 inches
Overall Width:
1.625 inches
Unthreaded Mounting Hole Diameter:
Between 0.150 inches and 0.158 inches
Distance Between Mounting Facility Centers:
1.930 inches
Pressure Switch Type:
Differential
Operating Tempurature Rating:
Between -73.0 degrees celsius and 150.0 degrees celsius
Mounting Method:
Bracket and unthreaded hole
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
5.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
15.75 actuation point pounds per square inch absolute and 14.75 deactuation point pounds per square inch absolute
Contact Voltage Rating In Volts:
30.0 dc at sea level single voltage
Pressure Connector Type:
Grooved, unthreaded internal single connection
Media For Which Designed:
Gas
Style Designator:
Cylindrical w/lugs
Shalf Life:

N/a

## NSN 5930-00-910-0042

Pressure Switch - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A048b0