## NSN 5930-00-910-1732

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-910-1732

# Thread Class:

2a single mounting facility **Thread Length:** 

0.375 inches single mounting facility

#### Overall Length:

1.531 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.750 inches single actuator

#### **Overall Diameter:**

1.250 inches

Nonturn Device Radius:

0.531 inches at 3: 00 o'clock

Individual Section Quantity:

1

### Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

#### **Operating Tempurature Range:**

-55.0/+85.0 degrees celsius

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

3 single section rear

#### Throw Quantity:

3 single section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### Thread Size:

0.375 inches single mounting facility

#### Contact Voltage Rating In Volts:

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

3 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes single section rear

#### Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-00-910-1732

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 500.0 milliamperes resistive load ac at sea level Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0