

View Online at <https://aerobasegroup.com/nsn/5930-00-910-5844>

Overall Length:

1.250 inches

Overall Height:

0.440 inches

Overall Width:

0.401 inches

Body Length:

0.776 inches

Body Width:

0.401 inches

Body Height:

0.251 inches

Unthreaded Mounting Hole Diameter:

0.156 inches

Distance Between Mounting Facility Centers:

1.000 inches

Longest Horizontal Distance Between Mounting Centers:

1.000 inches

Temperature Sensing Element Type:

Immersion well

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 200.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

2.5 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+35.00/+45.00 actuation point degrees fahrenheit and +35.00/+45.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

40.00 actuation point degrees fahrenheit and 0.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

115.0 ac at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A048b0